



KCD-F850 / F750

KCD-260

KCD-F772IR

Color Dome Camera / Color IR Dome Camera

KCD-F850 / F750 / 260 / KCD-F772IR

Function

KCD-F850

- 1/3" Interline Super HAD CCD (SONY)
- High Sensitivity
- Low Smear
- 550TVL (410K Pixels)

KCD-F750

- 1/3" Interline Super HAD CCD (SONY)
- High Sensitivity
- Low Smear
- 380TVL (270K Pixels)


KCD-260

- 1/3" Super HAD CCD (SONY)
- High sensitivity
- Low smear
- 420 TVL (270k pixels)
- 3.6mm Fixed Lens
- Audio (option)

KCD-F7721R

- 1/3" Interline Super HAD CCD (SONY)
- High Sensitivity
- Low Smear
- 550TVL(410K Pixels)
- 30 IR LED Sensors

Dimensions



Specifications

Model	KCD-F850, KCD-F750		KCD-260		KCD-F7721R	
	NTSC	PAL	NTSC	PAL	NTSC	PAL
Signal System	NTSC	PAL	NTSC	PAL	NTSC	PAL
Total Pixels	410K / 380K	470K / 440K	410K / 380K	470K / 440K	410K/380K	470K/440K
Pick-Up Device	1/3" Interline Super HAD CCD(SONY)		1/3" Interline Super HAD CCD(SONY)		1/3" Interline Super HAD CCD (SONY)	
Lens	Fixed Lens (f= 3.6 F#2.0)		Fixed Lens (f= 3.6 F#2.0)		Fixed Lens (f : 3.6, F#2.0)	
Signal Process	Digital Signal Process		Digital Signal Process		Digital Signal Process	
Scanning System	2:1 Interface		2:1 Interface		2:1 Interface	
Sync. System	Internal		Internal		Internal	
Scanning Frequency	59.94Hz (VD)	50Hz (VD)	59.94Hz(VD)	50Hz(VD)	59.94Hz(VD)	50Hz(VD)
Resolution	550 TV Lines(H)	380TV Lines(H)	420 TV Lines(H)		550 TV Lines(H)	
S/N Ratio	More than 48dB		More than 48dB		More than 48dB	
Standard Illuminance	2000 Lux (3200 K)		2000 Lux (3200 K)		2000 Lux (3200 K)	
Sensitivity	0.2 Lux F2.0		0.2 Lux F2.0		0 Lux (IR On)	
Video Output	1.0 Vp-Composite (75 Ω)		1.0 Vp-Composite (75 Ω)		1.0 Vp-Composite (75 Ω)	
Gain Control	On		On		On	
Flickerless	Off		Off		OFF	
White Balance	Auto		Auto		Auto	
Back Light	Off		Off		Off	
Shutter Speed	1/60~1/100,000 sec	1/50~1/100,000 sec	1/60~1/100,000 sec	1/50~1/100,000 sec	1/60~1/100,000 sec	1/50~1/100,000 sec
Power Source	DC 10V~14V		DC 10V~14V		DC 10V~14V	
Power Consumption	Less than 1.8Watts		Less than 1.8Watts		Less than 3.5Watts	
Infrared	-		-		30 Pieces IR	
Operating Temp.	-10 $^{\circ}$ C ~ 50 $^{\circ}$ C (Humidity : 0%RH~80%RH)		-10 $^{\circ}$ C ~ 50 $^{\circ}$ C (Humidity : 0%RH~80%RH)		-10 $^{\circ}$ C ~ 50 $^{\circ}$ C (Humidity : 0%RH~80%RH)	
Storage Temp.	-20 $^{\circ}$ C ~ 60 $^{\circ}$ C (Humidity : 0%RH~85%RH)		-20 $^{\circ}$ C ~ 60 $^{\circ}$ C (Humidity : 0%RH~85%RH)		-20 $^{\circ}$ C ~ 60 $^{\circ}$ C (Humidity : 0%RH~85%RH)	
Dome Size(mm)	100 \varnothing		100 \varnothing		100 \varnothing	
Weight	280 g		280 g		350 g	