



<b>Model No.</b>	<b>QH-W115SNH-3H</b>
<b>VIDEO</b>	
<b>Image Sensor</b>	1/3" SONY CCD
<b>TV System</b>	PAL/NTSC
<b>Synchronization</b>	Internal
<b>Horizontal Resolution</b>	650TVL
<b>Min. Illumination</b>	0Lux(IR-ON )
<b>S/N Ratio</b>	>50dB
<b>Video Output</b>	1Vp-p,75ohm, BNC
<b>Focal Length</b>	2.8-12mm VF Lens
<b>OPERATIONAL</b>	
<b>Shutter/AGC</b>	AUTO
<b>Backlight</b>	ON/OFF
<b>Mirror</b>	ON/OFF
<b>Brightness</b>	AUTO
<b>Contrast</b>	1-128
<b>Sharpness</b>	1-128
<b>Hue</b>	1-128
<b>Gain</b>	AUTO
<b>Motion detection</b>	ON/OFF
<b>Detect sense</b>	0-111
<b>Block display</b>	ON/OFF
<b>Monitor Area</b>	ON/OFF (4 AREA)

Privacy Mask	ON/OFF (4 AREA)
Camera ID	ON/OFF
ATR	ON/OFF
Noise Reduction	2D-DNR
NR Mode	Y/C(Y LEVEL 0-4;C LEVEL 0-4)
HLC	ON/OFF
OSD Menu	8 languages
White Pixel Detection and Compensation	Static and Dynamic
External Synchronization	Line-Lock
White Balance	ATW / PUSH / USER1 / USER2 / MANUAL / PUSH LOCK
BURST	ON/OFF
DELAY CNT	0-10
Infrared LED	42 Pieces
IR Distance	40 Meters
Infrared Spectrum	850nm
<b>ENVIRONMENTAL</b>	
Operation Temperature	-10°C~ +50°C
Storage Temperature	-20°C ~ +50°C
Vandal-proof Casing	IP66
<b>ELECTRICAL &amp; MECHANICAL</b>	
Power Consumption	DC12V 600mA
Adapter Requirement	DC12V 1.5A
Dimensions	200*171*83mm
Net Weight	1300g/pcs